

AGM:

## FILLING YOUR POWERSPORTS AGM BATTERY IS EASY.

The Powersports AGM is supplied dry with a separate acid pack and needs to be filled before use. Follow the steps below:



### 1 Prepare the battery

Place the battery on an even surface and remove the sealing strip.



### 2 Prepare the battery acid holder

Take the battery acid pack out of the plastic bag. Remove the sealing cap strips and set aside for later use. Do not remove or pierce the acid holder seals.



### 3 Fill the battery acid

Place the acid pack vertically on top of the battery, making sure that its six sealed openings are aligned with the six feed openings of the battery. Press the acid pack firmly downwards to pierce the seals – the acid will automatically start to flow into the battery. Make sure the pack is not tilted, as this can prevent the acid from flowing freely.



### 4 Check the battery acid flow

Ensure air bubbles are rising from each of the six feed openings and, if they're not, tap lightly on the acid pack. Leave the acid pack in place until it's empty. **Note:** never remove the acid pack during filling.



### 5 Remove the acid pack

Ensure that all of the battery acid has flowed out of the acid pack. If any acid remains inside, tap lightly on the holder as described above. Then carefully pull the acid pack out of the battery.



### 6 Seal the battery

Firmly press the sealing cap strip into the feed opening, ensuring that the strip is at the same level as the top of the battery. Then use both hands to evenly press the sealing cap strip downwards. This completes the filling process. Do not remove the sealing cap strip; no additional water or battery acid should be required. Please allow 20 minutes for the acid to be absorbed before fitting the battery.



**For safety, always wear protective gloves when filling the battery.**



Tradisjonelle blybatteri:

## FILLING YOUR POWERSPORTS FRESHPACK BATTERY IS EASY.

The Powerports Freshpack is supplied dry with a separate acid bottle and needs to be filled before use. Follow the steps below:



### Prepare the battery

Remove all plugs on top of the battery, by twisting or pulling them, and set aside for later use.



### Expose the vent

The vent plug on the side of the battery must be removed prior to filling.



### Open the acid bottle

Carefully cut off the acid bottle nozzle, leaving a minimum nozzle height of 10 mm. Please note: the acid bottle nozzle must not be removed too close to the container or the filling tube cannot be attached.



### Attach the filling tube

Attach the red filling tube firmly onto the nozzle of the acid bottle.



### Fill the battery with acid

Slowly fill the battery with acid, ensuring that all chambers are filled individually and evenly up to the 'max' mark. The amount of acid provided in the acid bottle is exactly the amount required.



### Dispose of the acid bottle

The completely empty acid bottle is recyclable. Please check with your local recycling services.



### Seal the plugs

After filling, completely seal the battery using the plugs removed in step 1. The vent plug on the side should not be re-inserted.



**For safety, always wear protective gloves when filling the battery.**